



Premier Tractor Hydraulic Fluid

APPLICATIONS

Premier Tractor Hydraulic Fluid is recommended for use:

- as a multifunctional fluid in tractors and other equipment employing a common fluid reservoir.
- in applications which call for the John Deere J20C lubricant specification.

It is fully compatible with equipment manufacturer's proprietary fluids and other fluids of this type.

Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

TYPICAL TEST DATA

<i>Product Number</i>	1162
<i>MSDS Number</i>	7912
Density at 15°C, kg/L	0.87
Viscosity, Kinematic cSt at 40°C cSt at 100°C	58.4 9.5
Viscosity, Brookfield cP at -35C°	40,000
Viscosity Index	145
Flash Point, °C(°F)	235(455)
Pour Point, °C(°F)	-42(-44)
Color	Orange

Minor variations in product typical test data are to be expected in normal manufacturing.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A Zimri DM LLC product

June 21, 2018

© 2018 Zimri DM LLC. All rights reserved.
All other trademarks are property of their respective owners.