



# PMI LUBRICANTS

2403 COMMERCE ROAD, RICHMOND, VA 23234 FOR MORE INFORMATION CONTACT US AT: Phone: (800) 243-5553 or (804) 231-0254 Email: lubeorders-richmond@pmilubes.com

# APPROVED FOR ALL SCR-EQUIPPED ENGINES

Certified DEF is formulated with high-quality urea and pure water to work with all diesel cars, trucks and power generators equipped with Selective Catalytic Reduction (SCR) technology.

### **CERTIFIED TO MEET ALL OEM SPECIFICATIONS:**

- \*API Certified
- \*ISO22241-1

### **CERTIFIED PRODUCT QUALITY:**

- \*Stored and handling using ISO22241-1 guidelines
- \*Date and batch code on each container
- \*Packaged using DEF-dedicated equipment to eliminate the

potential for cross-contamination.

#### CERTIFIED SAFE AND EASY TO HANDLE:

- \*Nonhazardous and nonflammable
- \*Nontoxic
- \*Premixed with pure water
- \*Two-year shelf life

## PACKAGING OPTIONS

1 gallon jug with dispensing nozzle

2.5 gallon jug with dispensing nozzle

55 gallon drums

330 or 275 gallon totes

Bulk

Tank Trucks









#### PRODUCT SPECIFICATIONS:

Certified DEF meets all API and ISO22241 specifications as outlined in the table below:

COMPONENT	LIMITS
Urea, Wt. %	32.5(±0.7)
Alkalinity as NH₃ Wt. %	<0.2
Biuret, Wt. %	<0.3
Insoluble Matter, mg/kg	<20
Phosphate (PO <sub>4</sub> ) <sub>1</sub> mg/kg	<0.5
Calcium, mg/kg	<0.5
Iron, mg/kg	<0.5
Copper, mg/kg	<0.2
Zinc, mg/kg	<0.2
Chromium, mg/kg	<0.2
Nickel, mg/kg	<0.2
Aluminum, mg/kg	<0.5
Magnesium, mg/kg	<0.5
Sodium, mg/kg	<0.5
Potassium, mg/kg	<0.5
Aldehydes, mg/kg	<5.0
PHYSICAL DATA	TYPICAL VALUE
Density @ 20°C, g/cm³ @ 68°F	1.0870-1.0930
Refractive index @ 20°C	1.3814-1.3843

