



## Premier Full Synthetic Transmission SAE 50W

**Premier Full Synthetic Transmission SAE 50W** is a premium quality full synthetic transmission fluid scientifically formulated using a combination of the highest quality synthetic base oils and state-of-the-art additive technology. It is formulated to provide stability under severe operating conditions, outstanding cleanliness, superior oxidation stability and excellent low temperature performance.

**Premier Full Synthetic Transmission SAE 50W** is manufactured to our highest standards of quality control that exceed industry standards. Every batch is laboratory tested from base stocks and additives to finished fluid to consistently deliver an exceptional level of performance and protection.

### Features:

- Superior Oxidation stability
- Lower Sump Temperatures
- Excellent Low Temperature Performance
- Improved Gear and Bearing wear protection
- Copper Cooler Protection
- Improved Fuel Economy >1%

**Premier Full Synthetic Transmission SAE 50W** is specifically formulated to meet and exceed the following performance requirements.

- API Service Category MT-1
- Eaton PS-386, PS-164 Rev 7, Roadranger® extended drain \*
- International TMS 6816 \*
- Mack Truck TO-A Plus \*
- Meritor O-81 (Publication TP-90014) \*
- ZF Freedomline \*
- Spicer Transmission Extended Drain
- Dana synchronized and non-synchronized transmissions

Premier Full Syn Trans SAE 50W	
Pour Pt °C	-36
Viscosity 40°C, cSt	113.66
Viscosity 100°C, cSt	17.92
Viscosity Index	175
Density (lb/gal) @ 60F	7.058
Specific Gravity	0.847
API Gravity	35.6
Foaming Sequences I, II, II	Pass
Color	L1.5

Product(s) manufactured in the USA. Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

Zimri DM LLC • 4643 Aerial Way Dr. • Roanoke, VA 24018, U.S.A. • Telephone 540 982-0600