



Premier Premium AW Hydraulic Oils (>6000 Hours)

Premier Premium AW Hydraulic Fluids are a high viscosity index hydraulic oil for use in mobile and industrial equipment operated in a wide range of sub-arctic and temperate climates. This offers superior shear stability and cold temperature performance.

Premier Premium AW Hydraulic Fluids are a premium anti-wear hydraulic fluid with outstanding low temperature characteristics. They are specially formulated for use in mobile equipment hydraulic circuits where wide temperature ranges are encountered.

Premier Premium AW Hydraulic Fluids can also be used for traditional in-plant hydraulic applications, and exceed most industry hydraulic fluid specifications, including Denison HF-2, HF-0 Commercial Shearing, Vickers, Sunstrand, Rexnord, and Cincinnati Milacron.

FEATURES

Premier Premium AW Hydraulic Fluids contain additive systems which impart characteristics most desired in these types of oils:

- Excellent thermal stability- contains the latest thermally stable zinc type additives, virtually eliminating the formation of heat- related sludging in electro-hydraulic servos associated with conventional zinc-type oils.
- Excellent rust protection
- Excellent anti-wear protection to pumps, motors, valves, and other hydraulic circuit components.
- Excellent anti-foam protection
- Excellent multi-temperature applications

APPLICATIONS

Premier Premium AW Hydraulic Fluids may be recommended for applications when a premium quality, anti-wear hydraulic oil is required by equipment manufacturers. The oils meet the rigorous performance requirements including Denison HF-O and HF-2, Cincinnati Milacron P-68, P-69, and P-70, Vickers M-2950-S and 1-286-S, DIN 51524 (Part II, III), ANSI 9005-E02-RO, ASTM D6158, GM LS-2, and AIST 126,127. Passes Vickers 35VQ25 Pump Test.

TYPICAL PROPERTIES

ISO GRADE	AW 32 Premium	AW 46 Premium	AW 68 Premium
Flash Point °C	177	199	199
Pour Pt °C	-37	-36	-31
Viscosity: @ 40°C, cSt	29.71	42.79	70.19
@ 100°C, cSt	5.54	7.56	11.74
Viscosity Index	126	145	163
Density (lb/gal) @ 60F	7.08	7.08	7.07
Specific Gravity	0.849	0.849	0.849
Gravity, API	35.1	35.1	35.2
Oxidation Stability, hrs	>6000	>6000	>6000
Color	L1	L1	L1

Product(s) manufactured in the USA. Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

Zimri DM LLC • 4643 Aerial Way Dr. • Roanoke, VA 24018, U.S.A. • Telephone 540 982-0600