



Premier Full Synthetic Multi-Vehicle ATF

PREMIER FULL SYNTHETIC MV ATF is a high-performance multi-vehicle transmission fluid that is specially formulated for use in most high viscosity planetary gear transmission applications. **PREMIER FULL SYNTHETIC MV ATF** is manufactured using premium synthetics and an additive package for superior protection from corrosion and wear as well as severe anti-shudder durability.

PREMIER FULL SYNTHETIC MV ATF is suitable for use in most passenger car and light truck applications including:

Aisin Warner AW-1*	DEXRON®	JWS 3324 (WS)*	Scion (All Vehicles)
Allison C-4	DEXRON®-II, IID, IIE	MAN 339F	Shell 3403, M115
Allison C-3	DEXRON®-IIIF, IIIG, IIIH	MAN 339 V1	Shell LA2634
Allison TES-295	DEXRON® VI*	MAN 339 V2	Subaru ATF, ATF-HP
Allison TES-389	Esso LT 71141	MAN 339 Z1	Suzuki ATF 3309
AS 68 RC (T IV)	Fiat, Typo T IV	MAN 339 Z2	Texaco ETL-7045E
Audi G 052 025	Ford FNRS	Mazda ATF-M III	Texaco ETL-8072B
Audi G 052 162	Ford MERCON® V	Mazda ATF-M V	Texaco N402
Audi G 055 025	(XT-2-QDR, XT-2-QSM SYN)	Mercedes Benz 236.1	Toyota T-III & T-IV
Audi 5HP LT 71141	Ford MERCON® V	Mercedes Benz 236.2	Toyota WS (JWS 3324)*
Audi G-052-162-A1 / A2	Ford WSS M2C 922 A1, 924-A	Mercedes Benz 236.5	Voith 55.6335.XX (G607)
Audi 5HP (ZF 5 HP 30)	(XT-8-QAW) (JWS 3309)	Mercedes Benz 236.6	Voith 55.6336.XX (G1363)
Audi G-055-025-A2(JWS 3309)	GM Type A	Mercedes Benz 236.7\	Volvo 97340
BMW ETL-7045, 7045E	GM T IV	Mercedes Benz 236.9	Volvo 97341
(83 22 0 026 922)	Honda DW-1	Mercedes Benz 236.10	VW G 052 025
BMW LA2634	Honda ATF-Z1	Mercedes Benz 236.11	VW G 052 162
BMW LT 71141	Hyundai/Kia Red 1, SP-II, III	Mitsubishi SP-II, SP-III, SP IV, J2	VW G 052 099
BMW 5 HP (ZF 5 HP 30)	Hyundai/Kia SP-IV*	NAG 1 (Jeep Cherokee)	VW G 055 025
BMW 5 HP LT 71141	Hyundai NWS-9638*	Nissan 402\	VW 5HP LT 71141
BMW MINI 83 22 0 402 413 9	Idemitsu K17	Nissan Matic-D, J, K	(Audi G-052-162-A1 / A2)
(JWS 3309)	Isuzu Bescom ATF II, III	Nissan Matic-S*	VW 5HP (ZF 5 HP 30)
Caterpillar Powershift TO-2	Jaguar ATF 3403 M115	Porsche ATF 3403 M115	ZF TE-ML 03D, 04D, 05L, 09,
Chrysler ATFs	Jaguar LT 71141\	Porsche LT 71141	11B, 14A, 16L, 17C
Chrysler Mopar AS 68 RC (T IV)	JASO 1-A	Saab T IV	ZF TE-ML 14B
Daewoo LT 71141	JWS 3309 (T IV)	Saturn T IV	ZF 5 HP 18FL / 19FL / 24A
			*Vis requirement not met

TYPICAL PROPERTIES	
Viscosity: cSt @ 40°C	33.64
cSt @ 100°C	7.41
Gravity, °API	34.66
Specific Gravity @ 60°F	0.8516
Viscosity Index	196
Brookfield Viscosity at -40°C, cP	10,300
Flash Point (PMCC), °C	>170
Pour Point, °F	-60
Appearance/Color	Red

Product(s) manufactured in the USA. Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

Zimri DM LLC • 4643 Aerial Way Dr. • Roanoke, VA 24018, U.S.A. • Telephone 540 982-0600