



Premier Saw Guide Oil

Premier Saw Guide Oil is a superior quality lubricant designed for service in Gang saw application.

Premier Saw Guide Oil is formulated with high-quality paraffinic base oils and a specially tailored additive package. It has high load-carrying capacity to protect against wear and seizure of sliding metal surfaces under heavy or shock-load conditions. It has good adhesion to metal surfaces in the presence of moisture and provides protection against rust and corrosion. It also has good oxidation resistance and thermal stability at high temperatures for long service life.

APPLICATION

Premier Saw Guide Oil is recommended for all brands of gang saw equipment.

TYPICAL PROPERTIES

ISO GRADE	ISO 68	ISO 100	ISO 150
Pour Point, °C	-32	-34	-34
Viscosity: cSt @ 40°C	69	98.2	146
cSt @ 100°C	9.53	13.3	17.5
Viscosity Index	117	136	132
Density (lb/gal)	7.26	7.16	7.19
Specific Gravity	0.871	0.859	0.862
Gravity, API	30.9	33.3	32.6
Color	L1.5	L1.5	L2.5

Product(s) manufactured in the USA. Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

Zimri DM LLC • 4643 Aerial Way Dr. • Roanoke, VA 24018, U.S.A. • Telephone 540 982-0600