



Premier SuperTack Bar and Chain Oil

Premier SuperTack Bar and Chain Oil is a lubricant designed to prevent rusting and reduce wear and link breakage thus extending bar and chain life. Oil requirement is low due to resistance to dropping and throw-off due to tackifier added to the oil.

TYPICAL APPLICATIONS

Premier SuperTack Bar and Chain Oil is a lubricant designed especially for lubrication of bar and chains in a variety of applications.

Typical Physical Properties Winter Grade:	
Specific Gravity @ 60 °F	0.8826
Viscosity @ 100 °C, cSt	8.71
Viscosity @ 40 °C, cSt	37.73
Viscosity Index	>220
Flash, (PMCC) °C	>200
Pour Point °C	-57°C

Typical Physical Properties Summer Grade:	
Specific Gravity @ 60 °F	0.8830
Viscosity @ 100 °C, cSt	10.67
Viscosity @ 40 °C, cSt	43.2086
Viscosity Index	>240
Flash, (PMCC) °C	>200
Pour Point °C	-54°C

The test results listed are typical properties only

Product(s) manufactured in the USA. Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

Zimri DM LLC • 4643 Aerial Way Dr. • Roanoke, VA 24018, U.S.A. • Telephone 540 982-0600