



Premier Premium Plus Syn Blend Motor Oils

Premier Premium Plus Synthetic Blend Motor Oils are fully licensed motor oils that meet or exceed the latest manufacturer's requirements for use in passenger car, SUV and light duty truck gasoline engines, powerboats, motorcycles and other stationary and mobile equipment. They are formulated from selected highly refined paraffinic base oils, synthetic base oils and carefully selected advanced additive technology to provide superior thermal and oxidation stability, corrosion and valve train wear protection and prevent the formation and accumulation of deposits and sludge.

APPLICATIONS

- When API licensed SN PLUS, SN, SM, SL, SJ oils are required
- When ILSAC GF-5, GF-4, etc. are required
- PREMIER 5W-20 can be used when Ford WSS-M2C945-A is specified
- PREMIER 5W-30 can be used when Ford WSS-M2C946-A or Chrysler MS-6395S is specified
- Meet or exceed the latest manufacturer's requirements for use in passenger car, SUV and light duty truck gasoline engines, powerboats, motorcycles and other stationary and mobile equipment.

BENEFITS

- Excellent fuel economy
- Superior synthetic blend protection against thermal breakdown
- Excellent protection from deposits at all operating temperatures
- Excellent cold-cranking capabilities
- Excellent anti-wear, anti-foam, bearing corrosion and anti-rust protection

TYPICAL PROPERTIES

Typical Test Data	5W20	5W30	10W30
Pour Point, °C	-45	-45	-40
Viscosity: cSt @ 40°C	47.2	60.4	64.6
cSt @100°C	8.2	10.1	9.8
Viscosity Index	148.5	156.3	135.7
CCS, cSt	5398.5	6028.5	5711
CCS, °C	-30	-30	-25
Density (lb/gal)	7.1	7.1	7.2
Color	L3	L3	L3

Product(s) manufactured in the USA. Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

Zimri DM LLC • 4643 Aerial Way Dr. • Roanoke, VA 24018, U.S.A. • Telephone 540 982-0600