



Premier TO-4 Fluid

PREMIER TO-4 Fluid is a high quality, power transmission fluid. It is formulated using the latest generation of highly refined base stocks, fortified with anti-wear, anti-oxidation, dispersants, and the newest technology of proven friction modifying additives. Meets or exceeds the high torque requirements of Caterpillar transmissions, wet-disc brakes, and final drives.

APPLICATIONS

Recommended for use in all Caterpillar TO-4, Allison C-4, API CF, Komatsu TO applications and transmissions where a Caterpillar TO-4 fluid is specified. Always refer to your owner's manual for specific requirements.

TYPICAL PROPERTIES

SAE Grade	10	30	50
Pour Point, °C	-44.3	-31.9	-32
Viscosity: cSt @ 40°C	35.7	93.8	240.1
cSt @ 100°C	6.2	10.9	20.3
Viscosity Index	120.8	100.3	98.3
Density (lb/gal)	7.2	7.4	7.5
Color	2.9	6.5	6.5

Product(s) manufactured in the USA. Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

Zimri DM LLC • 4643 Aerial Way Dr. • Roanoke, VA 24018, U.S.A. • Telephone 540 982-0600